



CEWELD SG CrMnMo Tig

certilas® THE FILLER METAL SPECIALIST

TYPE	8CrMo12 filler metal for welding similar type of steels. (Air 9117 - 8CD12)								
ANWENDUNGEN	CEWELD CrMnMo Tig finds its application in the aerospace and motorsports industries, and also in the repair of some tool steels. According AIR 9117 and LN 9425								
EIGENSCHAFTEN	CEWELD® SG CrMnMo EN 4332: FE-WL1805 (8CrMnMo12-4-9) wire is used for welding matching, and similar, composition base materials.								
KLASSIFIKATION	AWS A 5.28: ~ER 90S-B3 W.Nr. WL 1805								
GEEIGNET FÜR	30CrMoV12, 55NiCrMoV7, 55CrNiMo4								
ZULASSUNGEN									
SCHWEISSPOSITIONEN									
TYPICAL CHEMICAL ANALYSIS OF THE FILLER METAL (%)	C	Si	Mn	P	S	Cr	Mo		
	0.06	0.7	1.1	0.08	0.08	2.7	1		
MECHANISCHE GÜTEWERTE	Heat Treatment	R _{P0,2} (MPa)	R _m (MPa)	A5 (%)	Impact Energy (J) ISO-V RT	Hardness			
	720°C±15°C 2h	440	570	24	80	36 HRc			
RÜCKTROCKNUNG	Not required								
GAS ACC. EN ISO 14175	I1								