



CEWELD L-Ag60Sn

TYPE High Silver containing Cadmium free brazing alloy.

APPLICATIONS Joining: Steels, Cast iron, Copper, Copper alloys, Stainless steel, Nickel and Nickel alloys. Also

suitable for dissimilar joints between these metals. Do not use this alloy above working

temperatures of 200 °C

PROPERTIES High silver containing universal silver brazing alloy without Cadmium with low operating

temperature and high mechanical properties. Due to the addition of Sn. this alloy will show a bright looking joint and is more capillary then the standard silver brazing alloys. Flux/Paste: CEWELD

Super-Flux

CLASSIFICATION AWS A 5.8: BAg-18

EN ISO 17672: Ag 160

SUITABLE FOR Brazing: Steels, Cast iron, Copper, Copper alloys, Stainless steel, Nickel and Nickel alloys. Also

suitable for dissimilar joints between these metals.

APPROVALS

WELDING POSITIONS

PA PB PC PD PE PF PG

TYPICAL CHEMICAL ANALYSIS OF THE FILLER

METAL (%)

Cu	Sn	Ag
30	10	60

MECHANICAL PROPERTIES

Heat	R _{P0,2}	Rm	A5	Hardness
Treatment	(MPa)	(MPa)	(%)	
As Welded		420		HRc

REDRYING Not required

MELTING RANGE 600 - 730°C

GAS ACC. EN ISO 14175