



CEWELD AA 410

TYPE CEWELD® AA 410 is a stainless flux cored wire for Hardfacing.(13% Cr Steel)

APPLICATIONS Overlay of carbon and low-alloy steels for resistance to corrosion, erosion, or abrasion.

PROPERTIES CEWELD® AA 410 has higher hardness and is used in valve seats to obtain better galling resistance. Normally to obtain adequate ductility, preheat and post-weld heat-treatment are required .
CEWELD® AA 410 is a martensitic stainless steel that is heat-treatable. It has a nominal weld metal composition of 12% Chromium. These weld deposits are air hardenable that can normally be heat-treated after welding

CLASSIFICATION AWS A 5.22: E410T0-4
 EN ISO 14700: T Fe7
 W.Nr. 1.4009

SUITABLE FOR **Ferritic 13 % Chrome steel,**
 1.4000, 1.4001, 1.4002, 1.4003, 1.4006, 1.4008, 1.4021, 1.4024,
 X6Cr13, X6CrAl13, X10Cr13, X15Cr13, X20Cr13, G-X10Cr13
 AISI 410, 420

APPROVALS

WELDING POSITIONS



TYPICAL CHEMICAL ANALYSIS OF WELD METAL (%)	C	Si	Mn	P	Cr	Mo
	0.12	0.8	1.2	0.015	13.5	0.5

MECHANICAL PROPERTIES	Heat Treatment	R _{p0,2} (MPa)	R _m (MPa)	A ₅ (%)	Hardness
	As Welded				330 HB

REDRYING Not required

GAS ACC. EN ISO 14175 M21



CEWELD AA 410

AA 410 1,2MM

Packaging	KG/unit	EanCode
BS-300	15	8720663413826