

CEWELD NiCrBSi 6 Tig (Colmonoy 6)



TYPE Nickel based Tig filler metal for hardfacing and overlay applications.

APPLICATIONS NiCrBSi 6 TIG offers outstanding metallurgical and physical properties making them ideally suited

to solving wear mechanisms such as abrasion, erosion, corrosion and high-temperatures

encountered in service.

PROPRIÉTÉS This nickel based alloy offers superior wear protection, retaining its hardness up to 600°C (1000°F)

with significant resistance to oxidation.

CLASSIFICATION AWS A 5.21: ERNiCr-C

CONVIENT POUR Aircraft gas turbines, steam turbine powerplants, turbochargers and valves in reciprocating

engines, prosthetic devices, heat treating equipment, pollution control equipment, coal gasification

and liquefaction systems, and components in pulp and paper mills.

AGRÉMENTS

POSITIONS DE SOUDAGE



TYPICAL CHEMICAL ANALYSIS OF THE FILLER

METAL (%)

С	Ni	Cr	В	Si	Fe
0.7	Rem.	14	3	4.25	4

PROPRIÉTÉS MÉCANIQUES

Heat	R _{P0,2}	Rm	A5	Hardness
Treatment	(MPa)	(MPa)	(%)	
As Welded				55.5 HRc

ETUVAGE Not required

GAS ACC. EN ISO 14175