



## CEWELD L-Ag60Sn

TYPE High Silver containing Cadmium free brazing alloy.

APPLICATIONS Joining: Steels, Cast iron, Copper, Copper alloys, Stainless steel, Nickel and Nickel alloys. Also

suitable for dissimilar joints between these metals. Do not use this alloy above working

temperatures of 200 °C

PROPRIÉTÉS High silver containing universal silver brazing alloy without Cadmium with low operating

temperature and high mechanical properties. Due to the addition of Sn. this alloy will show a bright

looking joint and is more capillary then the standard silver brazing alloys.

Flux/Paste: CEWELD Super-Flux

CLASSIFICATION AWS A 5.8: BAg-18

EN ISO 17672: Ag 160

CONVIENT POUR Brazing: Steels, Cast iron, Copper, Copper alloys, Stainless steel, Nickel and Nickel alloys. Also

suitable for dissimilar joints between these metals.

**AGRÉMENTS** 

**POSITIONS DE SOUDAGE** 

PA PB PC PD PE PF PF

TYPICAL CHEMICAL ANALYSIS OF THE FILLER

METAL (%)

| Cu | Sn | Ag |
|----|----|----|
| 30 | 10 | 60 |

PROPRIÉTÉS MÉCANIQUES

| Heat      | R <sub>P0,2</sub> | Rm    | A5  | Hardness |
|-----------|-------------------|-------|-----|----------|
| Treatment | (MPa)             | (MPa) | (%) |          |
| As Welded |                   | 420   |     | HRc      |

ETUVAGE Not required

MELTING RANGE 600 - 730°C

GAS ACC. EN ISO 14175