

# CEWELD Ceramic Backing strip Ø shaped

**TYPE** Keramische backing strip Rond

**TOEPASSINGEN** Keramische onderlegstrips, ook wel bekend als lassteentjes, optimaliseren lasverbindingen door hogere lassnelheden, verbeterde doorlassing en stabiliteit van het lasbad te bevorderen. Ze zijn universeel inzetbaar voor diverse lasprocessen en posities, waardoor ze een veelzijdige oplossing vormen voor verschillende lasbehoeften.

**EIGENSCHAPPEN** Verkrijgbaar in de afmetingen:

Ø (mm)	Lengte (mm)
6	600
8	600
10	600
12	600
15	600

**CLASSIFICATIE**

**GESCHIKT VOOR** one side welding with high currents in shipbuilding, pressure vessel fabrication, machine construction, crane building, tank, and general steel building.

**GOEDKEURINGEN**

**LASPOSITIES**




(%)

**MECHANISCHE WAARDEN**

**HERDROGEN** Not required

**GAS ACC. EN ISO 14175**



# CEWELD Ceramic Backing strip Ø shaped

CERAMIC BACKING STRIP Ø SHAPED Ø 10MM	Packaging	KG/unit	EanCode
	0,6	60 meters per box	8720663410856
CERAMIC BACKING STRIP Ø SHAPED Ø 12MM	Packaging	KG/unit	EanCode
	0,6	48 meters per box	8720663410863
CERAMIC BACKING STRIP Ø SHAPED Ø 15MM	Packaging	KG/unit	EanCode
	0,6	42 meters per box	8720663410870
CERAMIC BACKING STRIP Ø SHAPED Ø 6MM	Packaging	KG/unit	EanCode
	0,6	90 meters per box	8720663410832
CERAMIC BACKING STRIP Ø SHAPED Ø 8MM	Packaging	KG/unit	EanCode
	0,6	72 meters per box	8720663410849