





# CEWELD SP 420-B

TYPE	High chromium stainless steel wire. Excellent wearing qualities and fair corrosion resistance.				
TOEPASSINGEN	The best all-purpose steel for machine element work. Metal spray wire for fairly corrosion resistant coatings with a hardness of approx. 50 HRC.				
EIGENSCHAPPEN	CEWELD® SP 420-B can be applied with the flame spray process and the electric arc process as well and offer extremely stable arc properties. The chemical cleaned surface assures excellent feeding properties. He is an 420 Type wire specially modified for spraying.				
CLASSIFICATIE	EN ISO	14919: X.mod type			
	W.Nr.	1.4028			
GESCHIKT VOOR	Shafts, Valves, seats, pistons etc.				
GOEDKEURINGEN					
LASPOSITIES					
TYPICAL CHEMICAL ANALYSIS OF THE FILLER METAL (%)	Si	Mn	Cr	C	Ni
	0.2	0.2	13	0.35	0.4
MECHANISCHE WAARDEN	Heat Treatment	R <sub>P0,2</sub> (MPa)	R <sub>m</sub> (MPa)	A5 (%)	Hardness
	As Welded				50 HRc
HERDROGEN	Not required				
GAS ACC. EN ISO 14175	M21				



# CEWELD SP 420-B

SP 420-B 1,6MM

Packaging	KG/unit	EanCode
BS-300	15	8720663409744

SP 420-B 2,0MM

Packaging	KG/unit	EanCode
K-415	15	8720663409799